



LEDIMAX®

LED-Controller LX-1165-RF

LEDIMAX FUNKSYSTEM Dimmer

- Single Color
- 1-channel output
- Compact design
- Connection for potential-free push-button



Specifications

Primary:

U_{in}: 12 - 48 Volt DC
I_{in}: 1 x 7,3 A

Secondary:

U_{out}: 1x (12-48) Volt DC
I_{out}: 1x 7A / 12-24V
1x 4A / 36V
1x 3A / 48V
P_{out} max: 84 W / 12 V
168 W / 24 V
144W / 36-48 V

Features:

- Connection of potential-free buttons possible
- 2.4 GHz mesh system (range up to 30 meters)
- 1-channel output switching / dimming
- Control via:

EasyThings APP (no gateway required)
Remote control
Radio or potential-free push-button

Dimensions [mm]: 95 x 37 x 20 (LxBxH)

Waterproof: IP20
Protection class: II
Operating temperature: -20°C bis +50°C
Certificates: CE, RoHS

Our products are subject to continuous further development. Changes and errors excepted.

IMPOLUX GmbH, Südstraße 4, 56288 Kastellaun, Germany
T +49 6762 9699100 F +49 6762 9699109
Email: info@impolux.de Internet: www.impolux.de